

Engine Make	Isuzu
Engine Model	4LE1NYGV-01
Engine Type	4-cylinder, naturally aspirated, diesel engine
Horsepower	32.1 hp
Displacement	2.2 l
Fuel Type	Diesel
Fuel Tank Capacity	56 gal.
Fuel Consumption	100% - 1.80 gph (6.81 lph) 75% - 1.35 gph (5.11 lph) 50% - 0.90 gph (3.41 lph)
Starting System	90A breaker
Battery	720CCA wet cell
OPERATIONAL	
Rated AC Output	3 Position Selector Switch: Single phase - 120 / 240V zig zag; Three phase - 120 / 208V low wye; Three phase - 277 / 480V high wye 16 kW / 16 kVA - standby, single phase 15 kW / 15 kVA - prime, single phase 20 kW / 25 kVA - standby, three phase 18 kW / 23 kVA - prime, three phase
AC Frequency	60 Hz
Continuous Operating Hours	31 hr.
Noise Level	68 dB(A) at 23 feet - prime power
MEASUREMENTS	
Length	105 in. (2.67 m)
Height	56 in. (1.42 m)
Width	68 in. (1.73 m)
Weight	Dry Weight: 1,640 lbs. (744 kg) Operating Weight: 2,038 lbs. (924 kg)
OTHER	
Tires	ST205/75R15 tubeless tires - 6 ply
Receptacles	(2) 120V 20A GFCI duplex outlets (Nema 5-20R type) (2) 240V 30A twistlock outlets (Nema L6-30R type) (2) 240V 50A twistlock outlets (Non-Nema 6369) Lug terminals for single and three phase output